

Humidity effect has been calculated for acetone sensor under 85-90%RH, created inside the chamber. The test results are shown in Figure 6. It is observed that there is an increase of 0.2V in high humidity sensing compared to the low humidity sensing. Artificial neural network was used to compensate these effects.




Figure 6. Acetone detection a). Under normal humidity b). Humidity=90% inside the chamber

The network is trained such that the MSE (Mean Square Error) is very low and Regression reaches 1. The trained network knowledge is stored in terms of weights and biases. The network is fixed with 180 I/O layer weights and 31 neuron biases. The trained network MSE is 2.75×10^{-27} and the total regression ratio is 0.9962 as shown in Figure 7. The relation between the acetone concentration and sensor response with humidity effect is already explained and is modeled in ANN tool [14].

From the collected samples it is observed that different values of voltage, resistance, pressure, humidity and temperature have been recorded for every person depending on their glucose levels and flow rate.




Figure 7. Network with R=0.99662

Figure 8 shows the network trained with regression coefficient R=1. Validation and Test results also show regression coefficient R=1 as shown in Figures 9 and 10. After training the network it has been tested with different breath inputs and the results compare closely with the actual glucose levels.




Figure 8. Trained network regression R=1




Figure 9. Network under validation R=1




Figure 10. Network under test R=1

From the results it is observed that the voltage and resistance are playing important roles in measuring the glucose level non-invasively whereas the other parameters affect the measurements very little. The temperature effect is more compared to other two parameters, the relative humidity and pressure. The training data is collected from non-diabetic patients with glucose

levels in between 80 mg/dL and 140 mg/dL and a few pre-diabetic patients with glucose levels in between 140 mg/dL and 180 mg/dL. Figure 11 (a) shows the variation in concentration of actual blood glucose levels of a patient over time. Figures 11b to 11f show the variation in different parameters during the non-invasive monitoring of blood glucose over time.




Figure 11. Variations in various parameters during monitoring of blood glucose levels over time: (a) actual concentration of blood glucose levels of a patient over time during invasive measurement; (b) voltage levels, (c) resistance, (d) pressure, (e) humidity and (f) temperature during non-invasive monitoring of blood glucose.

From the Figures 11 (a) to (f) it can be observed that if the glucose levels are high at some point the voltage will also be high and the resistance will go down and the other parameters are moderate. In some cases, albeit the glucose levels are high, voltage levels are low because of considerably low pressure, humidity and temperature levels, which indicate the person did not blow correctly into the mouth piece. These effects are minimized with the help of neural network tool.

V. CONCLUSIONS

In this study, the applicability of the breath acetone sensing method to the determination of glucose in human blood is demonstrated. We used acetone sensor for monitoring acetone levels in the exhaled breath and compared with actual blood glucose levels. We also considered the effects of the pressure, temperature and humidity parameters on the acetone sensing. This test involved studies of non-diabetic and pre-diabetic persons. We have also used Artificial Neural Network model for analyzing the data. The test results show that it is possible to measure the blood glucose levels via breath acetone sensing. The accuracy of the system can be improved with a large set of data.

REFERENCES

- [1] Chetan Sharma, Sachin Kumar, Anshul Bhargava, Shubhajit Roy Chowdhury. "Field programmable gate array based embedded system for non-invasive estimation of hemoglobin in blood using photoplethysmography." *International Journal on Smart Sensing and Intelligent Systems*, vol. 6, no. 3, pp. 1267- 1282, 2013.
- [2] Lieschnegg, M., M. Zacherl, B. Lechner, C. Weger, and A. Fuchs. "Non-invasive characterization of total hip arthroplasty by means of passive acceleration measurement." *International Journal on Smart Sensing and Intelligent Systems*, vol. 3, no. 1, pp. 75-87, 2010.
- [3] Gavin, J.R. "The Importance of Monitoring Blood Glucose". In *US Endocrine Disease; Touch Briefings*: Atlanta, GA, USA, pp. 1-3, 2007.

- [4] C. Turner, C. Walton, S. Hoashi, and M. Evans, "Breath acetone concentration decreases with blood glucose concentration in type I diabetes mellitus patients during hypoglycaemic clamps," *Journal of breath research*, vol. 3, no. 4, pp. 1-9, 2009.
- [5] Md. Mahbubur Rahman, A. J. Saleh Ahammad, Joon-Hyung Jin, Sang Jung Ahn and Jae-Joon Lee, "A Comprehensive Review of Glucose Biosensors Based on Nanostructured Metal-Oxides:" *Sensors*, vol. 10, pp. 4855-4886, 2010.
- [6] Tong Wang, Yanan Yu, Huifeng Tian and Jingbo Hu, "A Novel Non-Enzymatic Glucose Sensor Based on Cobalt Nanoparticles Implantation-Modified Indium Tin Oxide Electrode," *Electroanalysis*, vol. 26, pp. 2693–2700, 2014.
- [7] Saei, A. A., Dolatabadi, J. E. N., Najafi-Marandi, P., Abhari, A., De la Guardia, M.: "Electrochemical biosensors for glucose based on metal nanoparticles". *TrAC Trends in Analytical Chemistry*, vol. 42, pp. 216–227, 2013.
- [8] Dongyuan Zhai, Borui Liu, Yi Shi, Lijia Pan, Yaqun Wang, Wenbo Li, Rong Zhang, and Guihua Yu, "Highly Sensitive Glucose Sensor Based on Pt Nanoparticle/Polyaniline Hydrogel Heterostructures," *ACS Nano*, vol. 7, pp. 3540–3546, 2013.
- [9] S. Updike, G. Hicks, "The enzyme electrode", *nature publishing group*, vol. 214, pp. 986–988, 1967.
- [10] Luaibi, Ahmed Y., Ahmed J. Al-Ghusain, Asif Rahman, Mohammad H. Al-Sayah, and Hasan Al-Nashash. "Noninvasive blood glucose level measurement using nuclear magnetic resonance." *Proceeding of 8th IEEE GCC Conference and Exhibition (GCCCE)*, Muscat, pp. 1-4, 2015.
- [11] Ramasahayam, Swathi, Sri Haindavi Koppuravuri, Lavanya Arora, and Shubhajit Roy Chowdhury. "Noninvasive Blood Glucose Sensing Using Near Infra-Red Spectroscopy and Artificial Neural Networks Based on Inverse Delayed Function Model of Neuron." *Journal of medical systems*, vol. 39, no. 1, pp. 1-15, 2015.
- [12] U. M^uller, B. Mertes, C. Fischbacher, K. Jageman, and K. Danzer, "Non-invasive blood glucose monitoring by means of near infrared spectroscopy: methods for improving the reliability of the calibration models." *The International journal of artificial organs*, vol. 20, no. 5, pp. 285–290, 1997.

- [13] G. Dongmin, D. Zhang, L. Zhanga, L. Guangming “Non-invasive blood glucose monitoring for diabetics by means of breath signal analysis”, *Sensors and Actuators B: Chemical*, volume 173, pp. 106–113, October 2012.
- [14] S. Vashist, “Non-invasive glucose monitoring technology in diabetes management: A review”, *Analytica Chimica Acta*, vol. 750, pp. 16–27, 2012.
- [15] Mohammad Goodarzi, Sandeep Sharma, Herman Ramon, Wouter Saeys, “Multivariate calibration of NIR spectroscopic sensors for continuous glucose monitoring,” *TrAC Trends in Analytical Chemistry*, vol. 67, pp. 147–158, 2015.
- [16] Marco Righettoni, Anton Amann and Sotiris E. Pratsinis, “Breath analysis by nanostructured metal oxides as chemo-resistive gas sensors,” *Materials Today*, vol. 18, pp. 163-171, 2015.
- [17] Paweł Mochalski, Karl Unterkofler, Gerald Teschl, Anton Amann, “Potential of volatile organic compounds as markers of entrapped humans for use in urban search-and-rescue operations,” *TrAC Trends in Analytical Chemistry*, vol. 68, pp. 88–106, 2015.
- [18] Q. Zhang, P. Wang, J. Li, and X. Gao, “Diagnosis of diabetes by image detection of breath using gas-sensitive laps,” *Biosensors and Bioelectronics*, vol. 15, no. 5, pp. 249–256, 2000.
- [19] C. Deng, J. Zhang, X. Yu, W. Zhang, and X. Zhang, “Determination of acetone in human breath by gas chromatography–mass spectrometry and solid-phase microextraction with on-fiber derivatization,” *Journal of Chromatography B*, vol. 810, no. 2, pp. 269–275, 2004.
- [20] S. Chakraborty, I. Ray, A. Sen, and D. Banerjee, “Detection of biomarker in breath: A step towards noninvasive diabetes monitoring,” *Current Science*, vol. 94, no. 2, pp. 237–242, 2008.
- [21] Nasution, Tulus Ikhsan, Irwana Nainggolan, Sabar Derita Hutagalung, Khairil Rafezi Ahmad, and Zainal Arifin Ahmad. "The sensing mechanism and detection of low concentration acetone using chitosan-based sensors." *Sensors and Actuators B: Chemical*, vol. 177, pp. 522-528, 2013.
- [22] Hill, Darryl, and Russell Binions. "Breath analysis for medical diagnosis." *International Journal on Smart Sensing and Intelligent Systems*, vol. 5, no. 2, pp. 401-440, 2012.
- [23] Elosua, Cesar, Ignacio R. Matias, Candido Bariain, and Francisco J. Arregui. "Detection of volatile organic compounds based on optical fibre using nanostructured films." *International Journal on Smart Sensing and Intelligent Systems*, vol. 1, no. 1, pp. 123-136, 2008.

- [24] Yu-Feng Sun, Shao-Bo Liu, Fan-Li Meng, Jin-Yun Liu, Zhen Jin, Ling-Tao Kong and Jin-Huai Liu, "Metal Oxide Nanostructures and Their Gas Sensing Properties: A Review," *Sensors*, vol. 12, pp. 2610-2631, 2012.
- [25] V.K. Khanna, "Nanoparticle-based Sensors," *Defence Science Journal*, vol. 58, pp. 608-616, 2008.
- [26] C.-C. Wang, Y.-C. Weng, and T.-C. Chou, "Acetone sensor using lead foil as working electrode," *Sensors and Actuators B: Chemical*, vol. 122, no. 2, pp. 591–595, 2007.
- [27] J. Li, Y. Lu, Q. Ye, M. Cinke, J. Han, and M. Meyyappan, "Carbon nanotube sensors for gas and organic vapor detection," *Nano Letters*, vol. 3, no. 7, pp. 929–933, 2003.
- [28] D. Zohir and B. Hakim, "Enhancement of the neural network modeling accuracy using a submodeling decomposition-based technique, application in gas sensor," *Neural Computing and Applications*, vol. 21, no. 8, pp. 1981–1986, 2012.
- [29] Dmitriev, S. "Nanosensors engineering: I. structurally modulated sno2 nanowires." *International Journal on Smart Sensing and Intelligent Systems*, vol. 3, no. 4, pp. 643- 654, 2010.
- [30] Zvyagin, A. A., A. V. Shaposhnik, S. V. Ryabtsev, D. A. Shaposhnik, A. A. Vasil'ev, and I. N. Nazarenko. "Determination of acetone and ethanol vapors using semiconductor sensors." *Journal of Analytical Chemistry*, vol. 65, no. 1, pp. 94-98, 2010.
- [31] N. K. Suryadevara, S. C. Mukhopadhyay and L. Barrack, Towards a Smart Non-Invasive Fluid Loss Measurement System, *Journal of Medical Systems*, Springer (NON-INVASIVE DIAGNOSTIC SYSTEMS), February 2015, 39:38, 10 pages, DOI 10.1007/s10916-015-0206-6.
- [32] A. Reungchaiwat, T. Wongchanapiboon, S. Liawruangrath, and S. Phanichphant, "Home-made detection device for a mixture of ethanol and acetone," *Sensors*, vol. 7, no. 2, pp. 202–213, 2007.
- [33] Yadav, Lokendra. "Noninvasive biosensor for diabetes monitoring." *Asian Journal of Pharmaceutical and Clinical Research*, vol. 7, no. 3, pp. 206-211, 2014.